

28" COLOR VIDEO MONITOR WITH REAR CONTROLS

REF: 28MER400/AS



ALBIRAL PRO, S.L.
C/Gómez de Avellaneda, 32
28017 Madrid
SPAIN
Tel: +34 91 36 8 11 90
Fax: +34 91 368 11 97
E-mail: albiral@albiral.com

AVIALEC, S.L.
C/ Fátima 25
08512 Sant Hipòlit de Voltregà (Barcelona)
SPAIN
Tel.: +34 93 850 23 76 / 23 83
Fax: +34 93 850 25 50 / 23 72
Web: www.avialec.com
E-mail: avialec@avialec.com

SPECIFICATIONS		MODEL
		28MER400/AS
CRT	Size	28"
	Dot Pitch (mm)	0.8
	Screen ratio	4:3
	Invar Mask	
REQUIREMENTS	Anti glare, Anti static (AGAS)	<input type="checkbox"/>
	220Vac 50/60Hz	●
	110Vac 50/60Hz	<input type="checkbox"/>
	110/220Vac (switch)	<input type="checkbox"/>
	Max. Consumption	90W
	Operating temperature	10°C - 40°C
	Operating humidity (non-condensing)	10% - 80%
INPUTS / OUTPUTS	CVBS I/O	●
	S-VHS I/O	●
	RGB 9 Sub-D input	●
	RGB BNC I/O	<input type="checkbox"/>
	Priority system between CVBS and RGB	
	Audio I/O	●
CONTROLS	2 Internal speakers	●
	Analog controls (Digital Controls for /RS)	Brightness Contrast Color Volume (/AS)
	REMOTE CONTROL (IR) RS-232 / RS-485 (Digital controls)	
COLOR RESOLUTION	PAL	●
	PAL/SECAM	<input type="checkbox"/>
	PAL/NTSC (3,58MHz)	<input type="checkbox"/>
	PAL/NTSC (4,43MHz)	<input type="checkbox"/>
	PAL/SECAM/NTSC (3,58MHz)	<input type="checkbox"/>
	PAL/SECAM/NTSC (4,43MHz)	<input type="checkbox"/>
FEATURES	Max. Resolution	330 TVL (CVBS) 450 TVL (Y/C) 550 TVL (RGB)
	H. Synchronism	15,625±3% KHz
	V. Synchronism	48-62Hz
	Bandwidth	4.5MHz (CVBS) 6MHz (S-VHS) 8MHz (RGB)
	Blanking time	H - 11.9us V - 1.4ms
	CVBS signal	1Vp-p 75 ohm
	S-VHS signal	Y= 1 Vp-p 75 ohm C= 0.3 Vp-p 75 ohm
	RGB signal	0.75Vp-p 75 ohm
	White point coordinates	X:0.281 Y:0.311
	Stand-by	<input type="checkbox"/>
	Manual degauss	●
	Automatic degauss	●
	Cyclic degauss	<input type="checkbox"/>
MTBF	40,000h (excluding CRT)	
REGULATIONS	CE	●
CABINET	Metal cabinet with rear controls	●
PHYSICAL	Weight (Kg)	42
	Sizes W x H x D (±2mm)	610x482x425
PROTECTIONS	Vibrations	<input type="checkbox"/>
	Humidity	<input type="checkbox"/>

●	STANDARD
□	OPTIONAL
	NOT POSSIBLE

Rev 07/03

28MER400/AS