

# NVR8-8200PN-V2

## 8MP 8CH PoE NVR embedded with check point protection, and NDAA compliance

Provision-ISR's NVR8-8200PN-V2 is an easy-to-install solution for mid-sized installations (up to 8 channels). Check Point Quantum IoT Nano agent is integrated into this model. It provides an advanced threat prevention layer against the common attack vectors at runtime. The device equipped with 8 PoE ports and complies with NDAA demands, and provides you with everything you need for a trouble-free CCTV project.



## MAIN FEATURES

- NVR8-8200PN-V2 Video Input:
  - 8 Channels (PoE) Video Output:
  - HDMI – 4K
  - VGA Recording:
  - 8CH 8MP Real-Time
  - FPS: 200 (PAL) / 240 (NTSC) Playback:
  - Local: 8Ch Simultaneously
  - Remote: 8Ch Simultaneously Audio:
  - Input: 1CH + IPC Inputs
  - Output: 1CH + IPC Output
  - 2 Way Audio Alarm:
  - Input: Based on IPC only
  - Output: Based on IPC only Storage:
  - 1 x SATA (Up to 10TB each) Network:
  - 1 x RJ-45: 10/100/1000Mbps PTZ:
  - Network PTZ Support Power Supply:
  - DC 48V/1.875A Analytics: AI by IPC:
  - All Analytics Supported by the camera AI By NVR:
  - Up to 2Ch DDA1 (Sterile Area/Line Crossing) or
  - Up to 2Ch Face Detection Based on FW Version: v1.4.10
- Features subject to firmware version changes



<https://staging2.provision-isr.com>

## SPECIFICATIONS

3rd Party Cyber Protection	
<b>General</b>	Quantum IoT Nano agent by Check Point™
<b>Protection Methods</b>	Shell injection protection, File Monitor, Import-Table Protection, Dynamic-Memory Protection
NDAA Compliant	
<b>NDAA Compliant</b>	Yes
Video	
<b>Video Input</b>	8Ch over Network
<b>Output</b>	HDMI (4K, 1080P), VGA (1080P, 1280x1024, 1024x768)
<b>View Mode</b>	Mirrored
<b>Fish-Eye Dewarp</b>	Web Only
<b>Decoding Format</b>	H.265 / H.265+ / H.265S / H.264
<b>Decoding Capabilities</b>	1Ch – 8MP ; 4Ch – 2MP
Audio	
<b>Audio-specs-Input</b>	1CH RCA (Linear, 1kΩ) + IPC inputs
<b>audio-specs-Output</b>	1CH RCA (2.0 Vp-p, 1 kΩ) + IPC outputs
<b>Compression</b>	G.711A/G.711U
<b>Two Way Audio</b>	Yes
Analytics	
<b>Supported Analytics</b>	Camera Tampering, DDA2 With Object Classification, Line Crossing (DDA / Pixel Based), Sterile Area (DDA / Pixel Based), Object Monitoring, Object Counting (DDA), Crowd Gathering, People Intrusion, Smart Search, LPR, Thermal
<b>Analytics Channels (IPC Based)</b>	4Ch (Requires supporting IPC)
<b>Analytic Channels (NVR Based)</b>	Up to 2Ch DDA1 (Sterile Area/Line Crossing) or Up to 2Ch Face Detection (or their combinations)
<b>Face Recognition Rate</b>	N/A
Bandwidth	
<b>Incoming</b>	80Mbps

<b>Outgoing</b>	80Mbps
<b>Record/ Main Stream</b>	
<b>Real-Time Recording</b>	8CH 8MP Real-Time
<b>Record Type</b>	Video / Video + Audio
<b>Recording Modes</b>	Schedule, Manual, Motion, Sensor, Analytics, POS and all of the combinations
<b>16MP</b>	N/A
<b>12MP</b>	N/A
<b>8MP</b>	240FPS(NTSC)/200FPS(PAL)
<b>5MP and lower</b>	240FPS(NTSC)/200FPS(PAL)
<b>Master stream over network</b>	Up to 8CH@Recording Resolution
<b>Substream</b>	
<b>Resolution substream</b>	Depends on IPC
<b>Remote view</b>	
<b>Max Channel View</b>	40Ch (Limited to Outgoing Bandwidth Capacity)
<b>Remote Applications</b>	
<b>User Access</b>	64 Users online with Professional Authority Management
<b>Mobile App</b>	Provision Cam2 for iOS/Android
<b>PC/Mac Software</b>	Ossia VMS Standard / Enterprise
<b>Plug-in free Web-Browser</b>	Chrome, FireFox, Safari, Edge, Opera.
<b>Plug-in based Web-Browser</b>	Internet Explorer
<b>Playback</b>	
<b>Local</b>	8Ch
<b>Remote</b>	8Ch

<b>Search Mode</b>	DDA Object, Smart Search, LPR, Time-Slice, Time, Event, POS
<b>Backup</b>	
<b>USB</b>	2 USB 2.0 Port
<b>Backup Format</b>	AVI (Unencrypted) / Private Format (Encrypted / Unencrypted)
<b>Alarm</b>	
<b>Alarm-in</b>	Based on IPC only
<b>Alarm-out</b>	Based on IPC only
<b>Storage</b>	
<b>HDD</b>	1
<b>E-Sata Support</b>	No
<b>RAID</b>	N/A
<b>PTZ</b>	
<b>Connection</b>	Via Network
<b>Supported Controls</b>	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
<b>RS-485</b>	N/A
<b>Network</b>	
<b>Ethernet</b>	1000/100/10Mbps self-adaptive Ethernet interface
<b>Protocols</b>	TCP/IPv4/IPv6, DHCP, DDNS, NTP, SMTP, SSL/TLS, UPnP, P2P, RTSP, FTP, HTTPS, 820.1X, SNMP, Auto Report (Ossia VMS)
<b>ONVIF</b>	Full Device Support (Profile T/G, ONVIF Version 20.12)
<b>PoE</b>	
<b>PoE Ports</b>	8xRJ45
<b>Speed</b>	10/100Mbps (10Mbps under CCTV Mode)
<b>Standard</b>	PoE (IEEE802.3AF/AT)

# NVR8-8200PN-V2

<b>CCTV Mode</b>	Yes (Up to 200m and 10Mbps bandwidth)
<b>Total Power</b>	72W (Average 9W per Channel)
<b>Max. Power Output (Per Ch.)</b>	~25.5W
<b>Others</b>	
<b>Power Supply</b>	DC 48V/1.875A
<b>Power consumption (No HDD)</b>	10W
<b>Dimension</b>	W300xD249xH45mm
<b>Operation Temperature</b>	0°C~50°C